



Product Information Demotex K-2

Description	Thin release agent to spray on mould pattern or core boxes. This product contains organic silicon substances. Demotex K-2 is a solution of active substances in a solvent mixture.
Field of use	Moulding and core shop. Demotex K-2 is applicable to all common cold curable core and mould making processes as well as green sand casting.
Application	Demotex K-2 is to use undiluted in supply condition. The release agent should be sprayed thinly and evenly on the clean pattern surface or core box. The coat is applied by conventional spray equipment by hand or automatically by spray units. If used properly, a multiple demoulding of mould or core is possible.
Technical data	Colour: light yellow Density (20 °C): approx. 0,78 g/cm ³ Viscosity (23 °C): < 30 s Flash point: > 23 °C
Packaging	<u>Can á 20 kg and disposable drum á 160 kg</u>
Storage	Store Demotex K-2 tightly closed and frost-free in a dry, well-ventilated place; protect from heat and direct sunlight. Shelf life 12 months when properly stored inside in original unopened container. Close container tightly after using.
Regulations and information	Demotex K-2 is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15