



## Product Information Demotex KF

<b>Description</b>	Thin release agent to spray on mould pattern.  <b>Demotex KF</b> is a solution of active substances in mineral oil. This product contains silicone and is free from chlorinated hydrocarbons.
<b>Field of use</b>	Moulding - green sand casting.  <b>Demotex KF</b> is suitable for moulding complex contours. The release film is adhesive and resistant to heat and moisture, so that sand adhesion is largely avoided.
<b>Application</b>	<b>Demotex KF</b> is to use undiluted in supply condition.  The release agent should be sprayed thinly and evenly on the clean pattern surface. The coat is applied by conventional spray equipment by hand or automatically by spray units. If used properly, a multiple demoulding of mould or core is possible.
<b>Technical data</b>	Colour: yellowish Density (20 °C): approx. 0,82 g/cm <sup>3</sup> Flash point: > 160 °C
<b>Packaging</b>	<b><u>Can á 20 kg and disposable drm á 160 kg</u></b>
<b>Storage</b>	Store <b>Demotex KF</b> tightly closed and frost-free in a dry, well-ventilated place; protect from heat and direct sunlight. Shelf life 12 months when properly stored inside in original unopened container.
<b>Regulations and information</b>	<b>Demotex KF</b> is classified as non-hazardous according to the CLP regulation and therefore not subject to labeling. It corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15