



Product Information Demotex R-280

Description	Dissolved waxes with <u>propellant</u> to spray on mould pattern or core boxes.
Field of use	Moulding and core shop. Demotex R-280 is suitable for all cold curing foundry processes - such, for example, water glass-CO ₂ , Resol- CO ₂ , Resol-MF, cold resins, etc.
Application	Best effect is achieved with an evenly thin coating. Shake spray can well before use. Apply the release agent on the clean pattern surface or core box. If used properly, a multiple demoulding of mould or core is possible. Clean nozzle for longer brakes by holding spray can overhead. Do not spray Demotex R-280 towards a naked flame or any incandescent material. Solvent-vapours may form explosive mixtures with air, therefore provide for good ventilation – do not breathe vapours.
Technical data	Colour: colourless Density (20 °C): approx. 0,72 g/cm ³ Boiling point: approx. -44 °C
Packaging	<u>Box with 12 spray cans á 500 ml</u>
Storage	Protect Demotex R-280 from direct sunlight and temperatures above 50 °C. Keep away from open flames and other ignition sources. Pressurised container! Shelf life 36 months when properly stored inside in original unopened container.
Regulations and information	Demotex R-280 is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15