



Product information Graphit-Öl-Spray

Description	<p>Highly effective glide / lubricant, even under temperature stress. Graphit-Öl-Spray remains flexible even at low temperatures and does not become brittle. The product can be used in a temperature range up to +250 ° C.</p>						
Field of use	<p>Core shop / moulding, chill casting and maintenance.</p> <p>Graphit-Öl-Spray minimizes wear and causes noise damping. After evaporation of the solvent, a lubricating film of highest compressive strength is formed, which is tough adhesive, water-resistant and anti-corrosive.</p> <p>Graphit-Öl-Spray is therefore suitable as a lubricant for:</p> <ul style="list-style-type: none"> - <i>open drives</i>, such as gearwheels, gear racks, chains - <i>sliding guides</i>, such as slide valve, piston rods, ejector - <i>moving parts</i>, such as springs (of all kinds), wire ropes 						
Application	<p>Best effect is achieved with an evenly thin coating. <u>Shake</u> spray can <u>well before use</u>. Clean nozzle for longer brakes by holding spray can overhead.</p> <p>Do not spray the product towards a naked flame or any incandescent material. Solvent-vapours may form explosive mixtures with air, therefore provide for good ventilation – do not breathe vapours.</p>						
Technical Data	<table border="0"> <tr> <td>Density (20 °C):</td> <td>approx. 0,75 g/cm³</td> </tr> <tr> <td>Boiling point:</td> <td>approx. -44 °C</td> </tr> <tr> <td>Flash point:</td> <td>approx. -97 °C</td> </tr> </table>	Density (20 °C):	approx. 0,75 g/cm ³	Boiling point:	approx. -44 °C	Flash point:	approx. -97 °C
Density (20 °C):	approx. 0,75 g/cm ³						
Boiling point:	approx. -44 °C						
Flash point:	approx. -97 °C						
Packaging	<u>Box with 12 spray cans á 500 ml</u>						
Storage	<p>Protect Graphit-Öl-Spray from direct sunlight and temperatures above 50 °C. Keep away from open flames and other ignition sources. Pressurised container! Shelf life 24 months when properly stored inside in original unopened container.</p>						
Regulations and information	<p>Graphit-Öl-Spray is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.</p>						

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.