

Product information Multi-Spray 4X

Description Multi-Spray 4X is a transparent multi-function spray.

Field of use Core shop / moulding, chill casting and maintenance.

Multi-Spray 4X has the following properties

- Dissolves quickly and reliably all rusted and fixed parts of rust, resinified

greases, oil carbon and dirt.

- Protects metal surfaces effectively from corrosion.

- Eliminates squeaking and creaking noises.

- Maintains and cleans gently and displaces moisture.

Application Spray **Multi-Spray 4X** on stuck parts and leave shortly. To clean, wipe the

parts with a cloth or remove mechanically. For stubborn cases, repeat the

procedure.

Do not spray Multi-Spray 4X towards a naked flame or any incandescent

material.

Solvent-vapours may form explosive mixtures with air, therefore provide for

good ventilation – do not breathe vapours.

Technical Data Colour: Clear

Density (20 °C): approx. 0,62 g/cm³

Packaging Box with 12 spray cans á 500 ml

Storage Protect Multi-Spray 4X from direct sunlight and temperatures above 50 °C.

Keep away from open flames and other ignition sources.

Pressurised container!

Shelf life 24 months when properly stored inside in original unopened

container.

Regulations and information

Multi-Spray 4X is classified and labeled according to the CLP regulation

and corresponds to the current EC regulation.

Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety

data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 06/15

Technofond Gießereihilfsmittel GmbH • Am Pfaffensee 17 • 67376 Harthausen
Phone: +49-6344-969780 • Fax: +49-6344-9697855 • www.technofond.com • info@technofond.com